

# LIRDCSHL

## Features

- Vandalproof IR Dome Camera
- SONY Color CCD
- 540 TVL
- IR LED:  $\phi$  5X36PCS ,IR Distance: 30M
- Back Light Compensation(BLC)
- Auto White Balance(AWB)
- Lens: 4-9mm Manual Zoom Lens
- Dimension :  $\phi$  131 x 93(H) mm



## Specifications

Image Sensor	1/3"SONY ICX639BK CCD
Horizontal Resolution	540TV Lines Low Illumination
Pixels	PAL:752(H) $\times$ 582(V), NTSC:768(H) $\times$ 494(V)
TV System	PAL/NTSC
IR LED	$\phi$ 5 X 36 PCS
IR Series Distance	30 M
Lens	4-9mm Manual Zoom Lens
Sync System	Internal
IR Status	Under 10 Lux By CDS
Usable Illumination	0.0001Lux/F2.0
IR Power On	CDS Auto Control
S/N Ratio	$\geq$ 54dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )
Scanning System	NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:NTSC 1/60-1/100,000Sec
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max
White Balance	Auto
Power Source	DC12V 400mA
Dimension	$\phi$ 131 x 93(H) mm
Weight	800g