

Phaser® 3250

A4 Black and White Laser Printer

Compact, business-ready productivity

This powerful little printer is ready to support a single user or a small workgroup with fast, automatic two-sided printing, office-friendly convenience and outstanding overall value.



More performance for less

- **Get work done fast**, with a print speed of up to 28 ppm and a first-page-out time less than nine seconds.
- **Automatic two-sided printing** saves valuable time and paper.
- A network configuration — with both Windows, Mac and Linux compatibility — is truly business-ready.
- The 400 MHz processor ensures all jobs print quickly and accurately, even when they're loaded with graphics.


Convenience, flexibility

- A surprisingly small footprint makes it easy to position within quick reach.
- Standard 32 MB memory can expand to 160 MB for enhanced performance when your workload demands it.
- Add a second 250-sheet paper tray for a total capacity of 500 sheets.
- Print on custom sizes and a wide range of media, from transparencies and cardstock, to envelopes and postcards.
- Power Save and Toner Save modes help you spend less on electricity and consumables.

Always impressive results

- 1200 image quality print resolution adds visual impact to important jobs.
- PostScript® 3™ compatibility* and PCL® 6 emulation ensure your print jobs are always accurate.
- A 30,000-page monthly duty cycle handles big print volumes with ease.
- Outstanding Xerox quality, reliability and performance are backed by Xerox Service and Support with a standard one-year on-site warranty.

* available on DN configuration only



Print

A4

28 ppm

WxDxH:
364 x 369.4 x 239.2 mm

Phaser® 3250

Black and white laser printer



	Phaser® 3250D	Phaser® 3250DN
Speed	Up to 28 ppm	
Duty Cycle	Up to 30,000 pages / month	
Paper Handling	Bypass Tray: 1 sheet; Custom sizes: 76 x 127 mm to 216 x 356 mm Tray 1: 250 sheets; Sizes: A6 – A4 Tray 2: 250 sheets; Sizes: A6 – A4	
Paper input	Standard	
	Optional	
Paper output	150 sheets	
Automatic two-sided output	Standard	
Print		
First-page-out-time	As fast as 8.5 seconds	
Resolution	Up to 1200 image quality	
Processor	400 MHz	
Memory (std/max)	32 MB / 160 MB	
Connectivity	USB 2.0	10/100Base-TX Ethernet, USB 2.0
Language support	PCL® 6 and 5e emulations, IBM Pro Printer emulation, Epson emulation, GDI	PostScript® 3™ compatibility, PCL® 6 and 5e emulations, IBM ProPrinter emulation, Epson emulation, GDI
Print features	Watermarks, Poster printing, N-up, Fit to page, Scaling, Overlays, Booklets, Reduce/enlarge, Toner saver, Custom-size pages	
Warranty	One-year on-site warranty	

Device Management

Printer Setting Utility for Windows, 3250DN adds:
CentreWare® Internet Services, SNMP 1-2, Ethernal,
HTTP, TCP/IP (DN configuration)

Print Drivers

Windows® 2000/XP/2003 Server, Vista, Mac OS®X
version 10.3-10.5, Various Linux® OS including SUSE™ 8.2-9.2,
Red Hat® 8-9, Fedora™ Core 1-4, Mandrake 9.2-10.1

Font Support

1 bitmap, 45 scalable, 136 PostScript® fonts

Media Handling

Multipurpose Tray: 60 – 163 gsm
Media types: Plain paper, envelopes, transparencies,
labels, cardstock
Tray 1 and Tray 2 (optional): 60 – 105 gsm
Media types: Plain paper
Two sided printing: 75 – 90 gsm

Operating Environment

Temperature: Storage: 0° to 35° C
Operating: 10° to 32° C
Humidity: 20% to 80%
Sound pressure levels:
Printing: 54 dB(A)
Standby: 29 dB(A)
Warm-up time (from sleep mode): Less than 15 seconds

Electrical

Power: 220–240 VAC, 50/60 Hz
Power consumption: Standby: 70 W
Printing: 400 W
Power save: 11 W
ENERGY STAR® qualified

Dimensions (WxDxH)

364 x 369.4 x 239.2 mm
Weight: 11.88 kg
Optional 250-sheet Tray 2: 466 x 442 x 162 mm
Weight: 3.67 kg
Package Dimensions (WxDxH): 562 x 472 x 344 mm

Certifications

Listed UL 60950/CSA C22.2 No. 60950, CE Mark applicable
to Directives 2006/95/EC and 2004/108/EC

What Comes In The Box

- Phaser 3250 Printer
- Print Cartridge (2,000 print capacity¹)
- Software and Documentation CD
(with User Manual, Quick Installation Guide,
Warranty Statement, Registration Card)
- Power cord
- USB cable



Phaser 3250 shown with optional Tray 2

Supplies

Standard-Capacity Print Cartridge¹: 106R01373
3,500 std. page
High-Capacity Print Cartridge¹: 106R01374
5,000 std. pages

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 19752.
Yield will vary based on image, area coverage and print mode.

Options

250-sheet Tray 098N02194
128 MB Phaser Memory 098N02195

Supplies Recycling Program

Consumables for the Phaser 3250 are part of the Xerox
Green World Alliance Supplies Recycling Program. For more
information, please visit the Green World Alliance website
at www.xerox.com/gwa

