

KPC133



DOME CAMERA

● OVERVIEW

Equipped with a 1/3" Color CCD image sensor, this mini dome camera possesses satisfactory minimum illumination to provide clear and sharp images. It can be easily installed at any places for users to monitor a wider area.

● FEATURES

- (1) 420 TV lines of horizontal resolution and high quality picture
- (2) 1/3" color CCD sensor
- (3) Minimum Illumination 0.4 Lux / F2.0
- (4) S/N Ratio is more than 48dB (AGC off)
- (5) High reliability under long time operation

● SPECIFICATIONS*

Model	KPC133
Pick up Element	1/3" Color CCD image sensor
Number of Pixel	512(H) x 492(V) <NTSC> / 512(H) x 582(V) <PAL>
Resolution	420 TV lines
Min. Illumination	0.4 Lux / F2.0
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens Mount	C/CS mount changeable
Lens	f3.6mm / F2.0
Lens Angle	92.6°
Iris Mode	AES
AGC	Auto
White Balance	ATW
Video Output	1.0Vp-p composite, 75Ω
Power Source (10%)	DC12V
Current Consumption (10%)	90mA (280 mA)
Dimension (mm)**	100(∅) x 67(H)
iR Led	21

* The specifications are subject to change without notice.

* Dimensional Tolerance: ± 5mm