The compact printer that's perfect for personal use.

i-SENSYS
LBP6000

you can

Compact, energy-efficient desktop mono laser printer.

A space saving, affordable mono laser printer that's perfect for personal use. Delivering quality, maintenance-free prints, this energy-saving device is easy to use and exceptionally quiet.

18 PPM
7.8 SECONDS FIRST PRINT OUT TIME

SPACE-SAVING DESIGN

ENERGY EFFICIENT

ALL-IN-ONE CARTRIDGE

QUIET OPERATION

Key features

- Compact design making it ideal for even the smallest desk spaces
- Productive 18 ppm mono laser printing
- Quick warm-up time from sleep mode
- First Print Out Time of only 7.8 seconds or less
- Up to 2400 x 600 dpi resolution for high quality prints with Automatic Image Refinement
- Highly efficient 1.3 W power consumption in sleep mode
- Quiet operation and inaudible in Standby mode
- Convenient, easy to use All-in-One cartridge

What's in the Box
Main unit, Cartridge 725 starter, power cord, setup sheet and warranty card – with user software and manual CDs.

Dimensions (WxDxH)
359mm x 249mm x 198mm

Supported OS
Windows 7(32/64bit)/
Windows Vista(32/64bit)/XP(32/
64bit server 2008(32/64bit)/
server 2008 R2(64bit)/
2003 server(32/64bit)/ 2000
Mac 10.4.9 - 10.6.X
Linux (Web distribution only)

PRINT   COPY   FAX   SCAN

Canon

i-SENSYS LBP6000

Specifications

1 150-sheet multi-purpose tray
2 Cartridge 725

PRINTER ENGINE

Print speed	18 ppm mono (A4)[1]
Printing method	Monochrome laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	Up to 600 x 600 dpi
Warm-up time	10 sec or less
First Page Out Time	7.8 sec or less
Duty cycle	Max. 5,000 pages per month
Print margins	5mm top, bottom, left and right

MEDIA HANDLING

Paper input (Standard)	150-sheet multi-purpose tray
Paper output	100-sheet face down
Media types	Plain paper, Heavy Paper, Transparency, Label, Envelope
Media sizes	A4/B5/A5/LGL/LTR/EXE/16K/ Custom size COM10/Monarch/C5/DL/ISO-B5 width76.2×215.9mm x length 188×355.6mm
Media weights	Multi-purpose tray: 60 to 163 g/m²

GENERAL FEATURES

Power requirements	AC 220-240V (±10%), 50/60Hz (±2Hz)
Power consumption	Maximum: Approx 910 W or less Active: Average approx. 295 W Standby: Average approx. 1.6 W or less Sleep: Average approx. 1.3 W or less Typical Electricity Consumption (TEC): 0.5 kWh/week
Noise level	Sound power: Active: 6.34 B or less Standby: Inaudible Sound pressure: Active: 50 dB(A) Standby: Inaudible
Dimensions (W x D x H)	359mm x 249mm x198mm
Weight	approx. 5.0 kg
Operating environment	Temperature +10 to 30ºC Humidity 20% to 80% RH [no condensation]
Control panel	1 LED indicator 1 Operation key

CONTROLLER

Memory	Only buffer memory.
Printer languages	Canon Advanced Printing Technology (CAPT)
Interface and connectivity	USB 2.0 Hi-Speed
Operating systems compatibility	Win 7(32/64bit)/Win Vista(32/64bit)/XP(32/64bit) server 2008(32/64bit) / server 2008 R2(64bit)/ 2003 server(32/64bit)/ 2000 Mac OS10.4.9 - 10.6.X Linux (web distribution only)

CONSUMABLES

All-in-One cartridges	Starter: Cartridge 725 (700 pages[2]) Standard: Cartridge 725 (1,600 pages[2])

Standard disclaimer
All specifications subject to change without notice
Footnotes
1. The print speed may drop depending on the printer driver settings, paper size, paper type and number of pages printed
2. Based on ISO/IEC 19752