

Flexible space-saving mono laser printer with Wi-Fi, Ethernet and mobile connectivity

i-SENSYS
LBP6230dw

you can



Mobile and network ready Wi-Fi mono laser printer for small and home office use

Network and mobile ready with automatic 2-sided printing and a host of energy and time-saving features, this space saving Wi-Fi mono laser printer is ideal for any small or home office.

Key Features

- Versatile, compact Wi-Fi mono laser printer, ideal for small or home office use
- Wi-Fi and Ethernet connectivity for easy networking and wireless printing
- Print directly from smartphones and tablets with Canon Mobile Printing app
- There's no waiting for documents, thanks to Canon's Quick First-Print technologies plus 25 pages/minute
- Save time and money with automatic 2-sided printing
- Low power consumption and market leading energy efficiency
- Quiet operation lets you work without distraction
- Recyclable All-in-One print cartridge for maintenance free operation
- Stylish, space saving design that fits virtually anywhere

What's in the Box

Main Unit, Starter Cartridge, Power Cord, USB Cable, Setup Sheet, Warranty Card, User Software CDs

Dimensions (W x D x H)

379 mm x 293 mm x 243 mm

Supported OS

Windows Win 8.1(32/64bit)/Win 8(32/64bit)/Win 7(32/64bit)/Win Vista(32/64bit)/XP(32/64bit)/server 2012(32/64bit)/server 2012 R2(64bit)/server 2008(32/64bit) / server 2008 R2(64bit)/ 2003 server(32/64bit)

Mac OS 10.6 to 10.9

Linux *(Web distribution)/Citrix(FR2)



PRINT



COPY



FAX



SCAN



Wi-Fi

Canon

Specifications



1 250-sheet tray
2 Cartridge 726

| | |
|---|---|
| PRINTER ENGINE Print speed Printing method Print quality Print resolution Warm-up time First Page Out Time Duty cycle Print margins | 25 ppm mono (A4) Monochrome laser beam printing Up to 1200 x 1200 dpi Up to 600 x 600 dpi Approx 0.5 seconds from Sleep 10 seconds or less from power on Approx. 6 seconds Max 8,000 pages per month 5 mm-top, bottom, left and right |
| MEDIA HANDLING Paper input (Standard) Paper output Media types Media sizes Media weights | 250-sheet multi-purpose tray 1-sheet manual feed slot 100-sheet face down Plain paper, Heavy Paper, Transparency, Label, Index card, Envelope Multi-purpose tray: A4/B5/A5/LGL/LTR/EXE/16K/Custom sizes COM10/Monarch/C5/DL width 76.2 to 216 mm x length 187 to 356 mm Manual feed slot: A4/B5/A5/LGL/LTR/EXE/16K/Custom sizes COM10/Monarch/C5/DL/Index card width 76.2 to 216 mm x length 127 to 356 mm Multi-purpose tray: 60 to 163 g/m ² Manual feed slot: 60 to 163 g/m ² |
| GENERAL FEATURES Power requirements Power consumption Noise level Dimensions (W x D x H)mm Weight Operating environment Control panel | AC 220-240V(±10%) 50/60Hz(±2Hz) Maximum: Approx 1100W or less Active: Average approx 420W or less Standby: Approx 1.4 W or less Standby: Approx 2.2 W or less (Wi-Fi) Sleep: Approx 0.9 W or less Sleep: Approx 1.6 W or less (Wi-Fi) Typical Electricity Consumption (TEC): 0.7 kwh/week Sound power ¹ : Active: 6.77 dB or less Standby: Inaudible Sound pressure ¹ : Active: 52 dB(A) Standby: Inaudible 379 mm x 293 mm x 243 mm Approx. 7 kg temperature:10 to 30°C Humidity:20 to 80%RH (no condensation) 5 LED indicators, 4 operation KEY |

| | |
|---|---|
| CONTROLLER Memory Printer languages Interface and connectivity Operating systems compatibility | 64 MB UFR II LT USB 2.0 High-Speed, 10BASE-T/100BASE-TX, IEEE802.11b/g/n Win 8.1 (32/64bit)/Win 8(32/64bit)/Win 7(32/64bit)/Win Vista(32/64bit)/XP(32/64bit)/Server 2012(32/64bit)/Server 2012 R2(64bit)/Server 2008(32/64bit) / Server 2008 R2(64bit)/ 2003 Server(32/64bit)/ Mac OS X 10.6 to /Linux ² /Citrix (FR2 and later) |
| CONSUMABLES All-in-One cartridges | Standard: Cartridge 726 (2,100 pages ³) ⁴ |
| Footnote ^[1] Declared noise emission in accordance with ISO 9296 ^[2] Web distribution only ^[3] Based on ISO/IEC 19752 ^[4] Printer ships with 900 pages starter cartridge Standard disclaimers All specifications subject to change without notice | |

