Speed, quality and productive performance in a compact, elegant design.



Canon

you can

A compact A4 mono laser printer with all the capabilities small and medium-sized businesses demand.

This network ready, compact mono laser printer with duplex printing keeps you productive and offers the performance that dynamic small and medium-sized businesses demand.

Key features

- Compact, 33ppm mono laser printer keeps you productive
- Efficient automatic double-sided printing
- Network ready for easy integration and operation
- Fast First Print Out Time of just 6 seconds or less
- No waiting with Quick First-Print technologies
- Up to 2400 x 600 dpi print resolution with Automatic Image Refinement
- Max. 800-sheet paper capacity (250-sheet cassette, 50-sheet multi-purpose tray, optional 500-sheet cassette)
- Energy efficient and silent in standby
- Maintenance-free All-in-One cartridge for continuous high quality output

What's in the box

Main unit, 719 cartridge, power cord, quick setup guide and warranty card with user software and manual CDs.

Dimensions (W x D x H)

400mm x 376mm x 263mm

Supported OS

Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit / Server 2008 (32/64bit) / Server 2008 R2 (64bit) Mac OS 10.5 and up (Web distribution only) Linux (Web distribution only) Citrix





FΔX







Specifications:





1 50-sheet multi-purpose tray 2 250-sheet cassette 3 Cartridge 719 4 Cartridge 719H

PRINTER ENGINE Print speed Printing method Print quality Print resolution Warm-up time First Page Out Time Duty cycle Print margins	33ppm mono (A4) Monochrome laser beam printing Up to 2400 x 600 dpi with Automatic Image Refinement Up to 600 x 600 dpi Approx. 10 seconds or less from power on Approx. 6 seconds or less Max. 25,000 pages per month ¹ 5mm – top, bottom, left and right	CONTROLLER Memory Printer languages Interface and connectivity Software and printer management Operating systems compatibility	16 MB CAPT (Canon Advanced Printing Technology) USB 2.0 High-Speed, 10BASE-T/100BASE-TX NetSpot Device Installer, Remote User Interface (RUI) Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 / R2 (64bit) / Mac OS 10.5 and up ^{34.5} / Linux ^{3.4} / Citrix
MEDIA HANDLING Paper input (Standard) Paper input (Option)	250-sheet cassette 50-sheet multi-purpose tray 500-sheet cassette	CONSUMABLES All-in-One cartridges	Standard: Cartridge 719 (2,100 pages ⁶) High yield: Cartridge 719H (6,400 pages ⁶)
Paper niput (Option) Paper output Media types	150-sheet face down Plain paper, Heavy paper, Transparency, Label, Index card, Envelope	ACCESSORIES / OPTIONS Items	Paper Feeder PF-44 (500-sheet cassette)
Media sizes	Cassette (Standard and optional): A4, B5, A5, A6, Legal, Letter, Executive, 16K, Custom sizes: Width: 105.0mm to 215.9mm; Length: 148.0mm to 355.6mm Multi-purpose tray: A4, B5, A5, A6, Legal, Letter, Executive, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope B5, Envelope Monarch, Index Card, Custom sizes: Width: 76.2mm to 215.9mm; Length: 127.0mm to 355.6mm	1] Duty cycle is defined as the	
Media weights	Cassette (Standard and optional): 60 to 120 g/m ² Multi-purpose tray: 60 to 163 g/m ²		
Double sided printing	Automatic		
GENERAL FEATURES			
Power requirements Power consumption	220-240V (±10%) 50/60Hz (±2Hz) Maximum: Approx. 1170 W or less Active: Approx. 540 W Standby: Approx. 9 W Sleep: 1 W Typical Electricity Consumption (TEC): 1.9 kWh/week		
Noise level	Sound power ² : Active: 7.06 B or less Standby: Inaudible Sound pressure ² : Active: 54.2 dB(A) or less Standby: Inaudible		
Dimensions (W x D x H)	400mm x 376mm x 263mm		
Weight	Approx. 11.2kg		
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)		
Control panel	4 LED indicators 1 Operation key	J	











Canon Inc canon.com

Canon Europe canon-europe.com

European Edition © Canon Europa N.V., 2012



Speed, quality and productive performance in a compact, elegant design.



you can

A compact A4 mono laser printer with all the capabilities small and medium-sized businesses demand.

2 cartridges available: 719 and 719H

Sales Start Date: January 2013

The whole range consists of:

i-SENSYS LBP6020, i-SENSYS LBP6020B, i-SENSYS LBP6200d, **i-SENSYS LBP6310dn**, i-SENSYS LBP6670dn, i-SENSYS LBP6680x, i-SENSYS LBP6780x

Box Dimensions (W x D x H) 452mm x 517mm x 379mm

Box Weight 17.0kg

Packet style Pallet **Quantity of item** 8/12

MERCURY CODES

Name	Mercury Code	EAN Code
i-SENSYS LBP6310dn	_	_
OPTIONS		
Accessories	Mercury Code	EAN Code
Paper Feeder PF-44	3439B001AA	4960999630540
Consumables		
Cartridge 719	3479B002AA	4960999650289
Cartridge 719H	3480B002AA	4960999650319
EASY SERVICE PLAN		
3-Year return to base s	service i-SENSYS	
Details	Mercury Code	EAN Code
Detunis		
Physical Pack version	7950A528AA	4960999793320
Physical Pack version		
Physical Pack version 3-Year on-site next da		ategory A
Deterio	y service i-SENSYS C	ategory A EAN Code
Physical Pack version <u>3-Year on-site next da</u> Details	y service i-SENSYS C Mercury Code 7950A525AA	ategory A EAN Code
Physical Pack version 3-Year on-site next da Details Physical Pack version	y service i-SENSYS C Mercury Code 7950A525AA	ategory A

Canon

1



EAX



