

LIT90E

Specifications

Features	<ul style="list-style-type: none"> *IR LED: \varnothing 8X36PCS *IR LED working distance: 50M *Water resistance:IP66 Cable built-in bracket *Lens: 4-9mm Manual Zoom Lens External lens adjusting *Dimension:240x100x186 mm mm Weight:1.5Kg

Specifications

Model	LIT40ESHE	LIT40ESHHD	LIT40ESHL	LIT40ESL	LIT40EHF
Image Sensor	1/3"SONY				1/4" SHARP
Horizontal Resolution	ICX673AK CCD,700TV Lines Low Illumination, Effio, WDR, OSD, NR	ICX639BK CCD, 600TV Lines Low Illumination, WDR, OSD	ICX639BK CCD, 540TV Lines Low Illumination	ICX633BK CCD, 420TV Lines Low Illumination	RJ2421FA CCD,420 TV Lines Low Illumination
Pixels	PAL:795 (H) \times 596(V) NTSC :811 (H) \times 508 (V)			PAL:500(H) \times 582(V) NTSC:510(H) \times 492(V)	
Usable Illumination	0.001Lux/F2.0			0.01Lux/F2.0	
TV System	PAL/NTSC				
IR LED	\varnothing 5 X 36 PCS				
IR Series Distance	30 M				
Lens	4-9mm Manual Zoom Lens (Optional)				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
IR Power On	CDS Auto Control				
S/N Ratio	\geq 48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75 Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max				
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max				
White Balance	Auto				
Power Source	DC12V 400mA				
Dimension	200x171x83mm				
Weight	1300g				