HP Color LaserJet CM1312 MFP series





Enable productivity with HP's lowest-priced colour laser MFP, an easy-to-use multifunction device that delivers high quality colour output. Print and copy with speeds up to 12 ppm black and 8 ppm colour and enjoy easy flatbed scanning and faxing¹.



HP Color LaserJet CM1312 MFP



HP Color LaserJet CM1312nfi MFP An excellent choice for workteams of 2-5 users in unmanaged micro- and small-businesses who need an affordable, reliable, easy-to-use multifunction device to produce a range of business documents.

Easily achieve professional-quality results with HP's most affordable colour laser MFP with fax².

Deliver more effective business communications with colour from a single, compact LaserJet MFP solution from HP. Enjoy cost and space savings from HP's lowest-priced colour laser MFP featuring advanced print, scan, copy and fax². Impress with professional print and copy results achieved with HP ImageREt 3600. Next generation HP ColorSphere toner and all-in-one print cartridge design simplifies maintenance and delivers high gloss, vibrant colours, crisp detail, and realistic photo quality.

Increase productivity and results with this high performance, high quality HP colour laser MFP.

Get professional quality prints and copies quickly in up to 12 ppm black, and up to 8 ppm in colour. Increase everyday efficiency with advanced print, copy, scan and fax² functionality in one compact, easy-to-use solution. Share functionality with integrated 10/100 Base TX networking², or connect directly to your PC via the Hi-Speed USB port. Enjoy unattended copying, scanning and faxing and work more effectively with an integrated 50-page automatic document feeder².

This innovative HP Color LaserJet MFP is very easy to install, use, share and maintain.

Easily setup, install, and configure the MFP in just a few clicks. Simple to use with set-up wizards and an intuitive control panel with two line, 16 character LCD. Easily scan flat, bound documents, or even objects. All-in-one Original HP print cartridges are clean and easy to install and replace. Enjoy easy and consistent set up and printing across a network with HP's new Universal Print Driver. Deploy, manage, monitor and maintain about 15 HP LaserJets with HP Easy Printer Care Software.

2 Available with HP Color LaserJet CM1312nfi MFP.

Technical specifi				ring information
Print technology Print speed	Laser	lour: Up to 8 ppm. First page out black: < 25.5 sec (from ready mode). Colour: < 31.5 sec (from	CC430A	MFP; preinstall introductory 750-pa
rnn speed		ries depending on the system configuration, software program, and document complexity.		black, cyan, magenta, ar
Processor	450 MHz. Freescale Coldfire® V5X embedded processor			yellow HP Color LaserJ
Memory	CM1312: 128 MB; CM1312			, print cartridges wi
Print	Quality	HP ImageREt 3600		ColorSphere toner; in-bo
	Resolution	A4 black: Up to 600 x 600 dpi. Colour: Up to 600 x 600 dpi		documentation (Gettir
	Printer languages	HP PCL 6, HP Postscript level 3 emulation, HP PCL 5c emulation		Started Guide, suppo
	Economical printing	Manual duplexing and N-up printing (multiple pages per sheet) features save paper.		flyer); CD (User's Guide ar
	Typefaces/fonts	80 TrueType internal scalable PCL 6, 80 TrueType internal scalable Postscript		device software); pow cable; control pan
	Duty cycle	Up to 30000 pages pages per month		faceplate; Readiris PR
	Recommended monthly page	250 to 1500		OCR software ar
	volume			registration card, Marketir
	Print margins (mm)	Top: 4.2 mm. Left: 4.2 mm. Right: 4.2 mm. Bottom: 4.2 mm		Starter Kit (specialty med
	Printer Smart Software	Up to ImageREt 3600 print quality with HP PCL 6 and Postscript level 3 emulation print drivers;		samples, discounts
	Features	manual duplex and booklet printing; N-up printing; collation, watermarks; accepts a variety of		partner offerings, docume
		laser paper sizes and types including matte, soft gloss, and high gloss laser photo paper, mono transparencies, cover paper, cardstock, brochure paper, labels, envelopes, and more		template
Fax	Modem speed	36.6 Kbps	CC431A	HP Color LaserJ
	Telecom compliance	Telecom: ES 203 021, R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe), FCC		CM1312nfi MFP 33
		Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand),		Super G3 fax, 50-she
		AS/ACIF S002: 2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11		automatic document feede
		(Taiwan), HKTA 2011 (Hong Kong SAR), YD514, YD/T589, YD703, GB3382 (China) other		10/100 networkin additional 32MB
		Telecom approvals as required by individual countries		memory, 2.4-inch colo
	Fax memory	Up to 250		graphics display, pho
	Fax resolution	Standard: 203 x 98 dpi. Fine: 203 x 196 dpi. Superfine: 300 x 300 dpi (no halftone)		memory card slo
	Quick dialing	4		momory cara dia
Scan	Туре	Colour scanning: Yes. File Formats: BMP, GIF, JPG, PNG, TIF, PDF		
	Scan resolution	Optical: Up to 1200 dpi. Enhanced: Up to 19,200 dpi		
	Bit depth Grey scale levels	24-bit 256		
	Twain version	TWAIN compatible Version 1.9		
	Scan input modes	Remote initiated scanning via HP Director, TWAIN-compliant or WIA-compliant software, HP		
		Solution Center software		
	Scannable area	Minimum media size: 54 x 70 mm. Maximum media size: 216 x 297 mm		
	Margins for scanned items	Left: 4.2 mm. Top: 4.2 mm. Right: 4.2 mm. Bottom: 4.2 mm		
	Scanner smart software	Twain, WIA Drivers; HP Scanning software; scan key on control panel for scan-to-e-mail and		
	features	scan-to-folder capability; automatic scan calibration, scan image straightening, cropping, and		
		image enhancement; HP Document Viewer for document annotation capability and HP Photosmart		
<u>^</u>	<u> </u>	Premier software for advanced image enhancement; Readiris PRO text recognition software		
Сору	Copy speed	Up to 12 cpm		
	Copy resolution Multiple copies	Up to 600 x 600 dpi Up to 99		
	Reduce/enlarge	25 to 400%		
		es Up to 99 multiple copies, scan once print many, collation, reduce/enlarge from 25 to 400% (with		
		page-size presets), fit to page, two or four pages to one page, customisable copy presets, contrast		
		(lighter/darker), resolution (copy quality), network protocols supported		
Media handling	Input:	Capacity Weight Size		
	Tray 1	sheets: 150, envelopes: 60 to 176 g/m² (up to 200 g/m² A4, A5, B5, A6 (ISO, JIS), 76 x		
		10 with HP laser cover papers, up to 127 to 216 x 356 mm		
		220 g/m ² with HP laser glossy		
		photo papers)		
	Output:	Sheets: Up to 125. Envelopes: Up to 10. Transparencies: Up to 50		
	Duplex printing:	Manual (driver support provided)		



Technical specifications

Ordering information

•			-	
Media types	Paper (bond, brochure, colour, glossy, letterhead, photo, plain, preprinted, prepunched, recycled, rough), transparencies, labels, envelopes, cardstock		Connectivity	
Interface and connectivity	CM1312: 1 Hi-Speed USB (compatible with USB 2.0 specifications) port; CM1312nfi: Built-in 10/100 wired Ethernet network connectivity with 1 RJ-45 port, 1 Hi-Speed USB (compatible with USB 2.0 specifications) port	Q6264A	HP 1.8m USB cable	
Operating systems compatibility	Microsoft® Windows® 2000, Server 2003, XP Home, XP Media Center, XP Professional, XP Professional x64, XP Tablet PC; Certified for Windows Vista®; Mac OS X v10.3 or higher; Novell® NetWare 3.2, 4.2, 5.x, 6; HP-UX 10.20, 11.x; RED HAT Linux 6.x or higher; SUSE Linux 6.x or higher; Solaris® 2.5x, 2.6, 7, 8, 9, 10 (SPARC®); AIX® 3.2.5 or higher; MPEiX; Citrix® MetaFrame; Terminal Services. Latest supported operating systems and print drivers available at: http://www.hp.com/support/cljcm1312mfp	 Service & support UE663E HP Care Pack, Return to HP, 2 years UE199E HP Care Pack, Return to HP, 3 years UE666PE HP Care Pack, Post Warranty, Return to HP, 1 year UE665E HP Care Pack, Next Business Day On-Site Response, 2 years UE200A/E HP Care Pack, Next Business Day On-Site Response, 3 years UE609PE HP Care Pack, Post Warranty, Next Business Day On-Site Response, 1 year H3110E HP Care Pack, Installation & Configuration For 1 Network Printer H4513E HP Care Pack, Installation For 		
Network operating systems compatibility	Optional: Windows Vista® Ultimate, Home Premium, Home Basic, Business, Enterprise, Ultimate-64bit, Home Premium-64bit, Home Basic64bit, Business-64bit, Enterprise-64bit, Microsoft® Windows® XP Home, XP Professional, XP Media Center, XP Tablet PC; Mac OS X v10.3, v10.4, v10.5; Leopard, Linux PS3 (driver only), Unix PS3 (driver only), Citrix® (PDL, print driver only-supports NT OS's). Driver only: Windows Vista® Starter, Microsoft® Windows® XP Professional-64bit, Microsoft® Windows® 2003 Server, 2003 Server-64bit; 2000			
Minimum system requirements	Microsoft® Windows® Server 2003: any Pentium® II processor or higher, 64 MB RAM, 50 MB available hard disk space, SVGA 800 x 600 monitor with 16-bit colour (print driver, scan driver only); Microsoft® Windows® 2000, XP Home, XP Professional: any Pentium® II processor (Pentium® III or higher recommended), 128 MB RAM, 250 MB available hard disk space, SVGA 800 x 600 monitor with 16-bit colour, Internet Explorer 5.5 or higher (full install); 1 GHz processor, 512 MB RAM (Windows Vista®), check user guide for minimum hard drive space); CD-ROM drive, USB port. Mac OS X v 10.3.9, v10.4.x, v10.5.x; PowerPC G3, G4, or G5 processor; Intel® Core processor; 80 MB RAM, 30 MB available hard disk space; USB port; CD-ROM drive			
Standard software	CM1312: HP Toolbox, HP LaserJet Scan, TWAIN 1.9 or WIA scanner drivers, Readiris PRO text recognition software (not installed with other software, separate installation required), printer drivers (HP PCL 6, HP Postscript level 3 emulation), installer/uninstaller, HP Director (Macintosh); CM1312nfi: HP Toolbox, HP LaserJet Scan, TWAIN 1.9 or WIA scanner drivers, HP LaserJet Fax, HP Fax Setup Wizard, HP Fax software, Readiris PRO text recognition software (not installed with other software, HP Fax software, HP Fax software, HP Fax software, Readiris PRO text recognition software (not installed with other software, HP Fax Setup Wizard, HP Fax software, Readiris PRO text recognition software (not installed with other software, HP CL 5, HP PcL 5e, HP Postscript level 3 emulation), installer/uninstaller, HP Director (Macintosh); Drivers on the web: CM1312: Installer, print drivers, HP Scan software, HP Toolbox for management and support, Readiris PRO text recognition software, HP Software Update, HP Web Jetadmin, Enterprise Installer; CM1312nfi: Installer, print drivers, HP Software Update, HP Web Jetadmin, Enterprise Installer; PRO text recognition software, HP Software Update, HP Web Jetadmin, Enterprise Installer; RPO text recognition software, HP Software Update, HP Web Jetadmin, Enterprise Installer; PRO text recognition software, HP Software Update, HP Web Jetadmin, Enterprise Installer; RPO text recognition software, HP Norbox for management and support, Readiris PRO text recognition software, HP Norbox for Management and Support, Readiris PRO text recognition software, HP Norbox for management and Support, Readiris PRO text recognition software, HP Norbox for Management and Support, Readiris PRO text recognition software, HP Norbox for Management and Support, Readiris PRO text recognition software, HP Norbox for Management and Support, Readiris PRO text recognition software, HP Norbox for Management and Support, Readiris PRO text recognition software, HP Norbox for Management and Support, Readiris PRO text re	1 HP Printer For a complet	e list of supplies, nd services, please refer	
Control panel	CM1312: Intuitive control panel with 2-line character display alternating message screen, device/supplies status view, copy controls, scan controls, setup, reduce/enlarge, lighter/darker, and cancel buttons; CM1312nfi: Intuitive 6.1 cm control panel with colour graphic rotating display, alternating message screen, device/supplies status view, Ready LED, Error LED, Copy controls, Scan controls, Fax controls, Black/Colour controls, Photo controls, Numeric, Setup, Cancel, Help, and Back buttons.			
Power	Requirements: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz). Consumption: 295 watts (printing), 310 watts (copy/scan), 21 watts (ready), 7.2 watts (sleep), 0 watts (off)			
Dimensions (w x d x h)	Out of package: CM1312: 437 x 455 x 405 mm; CM1312nfi: 497 x 490 x 485 mm. Packaged: CM1312: 600 x 500 x 545 mm; CM1312nfi: 600 x 600 x 589 mm			
Weight	Out of package: CM1312: 21.2 kg; CM1312nfi: 24.7 kg. Packaged: CM1312: 27.25 kg; CM1312nfi: 35.34 kg			
Printer management	HP Toolbox, HP Web Jetadmin, HP Embedded Web Server, HP Easy Printer Care Software			
Operating environment	Operating temperature: 15 to 32.5° C. Recommended operating temperature: 20 to 27° C. Operating humidity: 10 to 80% RH. Operating humidity recommended: 20 to 70% RH. Storage temperature: 20 to 40° C. Storage humidity: 10 to 95% RH. Noise level per ISO 9296: sound power: LwAd 6.1 B(A) (printing at 12 ppm), 6.4 B(A) (maximum copy/scan), inaudible (ready). Sound pressure: LpAm 47 dB(A) (bystander), 50 dB(A) (bystander copy/scan), inaudible (bystander ready)			
Certifications	CISPR 22: 2005/EN 55022: 2006 Class B, EN 61000-3-2: 2000+A2, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1+A2, FCC Title 47 CFR, Part 15 Class B (USA), ICES-003, Issue 4, (Canada), GB9254-1998, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries. Regulatory standards: IEC 60950-1 (International), EN 60950-1+A11 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A1+A2 (Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries. ENERGY STAR: Yes			
	One-year, return to authorised service centre, limited hardware warranty			

http://www.hp.com/uk



© Copyright 2008 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

